

# Hogedrukreinigers

Maxima LP (koud en warm water)

Reinigingstechniek B.V.  
**Lamers**



## Standard equipment:



## Optional:

- Hose-reel with brake without hose code 6.608.0005
- Antiscale LC-PRECAL (pcs. 4 x 5 lt.) code 3.697.0044

## Equipped with:

- 4 poles electrical motor (1450 RPM) and thermal protection and water cooling
- Three ceramic pistons, brass linear pump head with built-in bypass valve
- Suction and delivery S/S valves.
- Automatic Stop System late shut down protection 24V
- Vertical burner with high thermal efficiency
- Header tank with antiscale tank
- Adjustable detergent delivery with built-in tank for direct suction (high-pressure delivery).
- Auxiliary motor for burner air-cooling and two ways fuel pump
- Glycerine pressure gauge
- Power cable (m 5)
- Temperature regulation gauge
- Gun with swivel hose fitting
- Low voltage control switches
- Tough steel main frame

### Maxima 2015 LP

Code	8.622.0904
Operat. pressure bar	30 ÷ 200
Operat. pressure psi	2900
Delivery rate l/h	450÷ 900
Temp. max	140° C
Power ass. W	7300
RPM	1450
Voltage	400V-50 Hz

