

A5 EVO



Watch the video on youtube:
www.youtube.com/fasavideo

Technical data:	A5 EVO 50 E	A5 EVO 50	A5 EVO 50 T
Code	8.527.0005	8.527.0006	8.527.0008
power supply	230 V - 50 Hz	24V	24V
scrubbing width	500 mm	500 mm	500 mm
squeegee width	800 mm	800 mm	800 mm
max working capacity	2000 m ² /h	2000 m ² /h	2000 m ² /h
detergent tank capacity	44 l	44 l	44 l
recovery tank capacity	50/60 l	50/60 l	50/60 l
traction	mechanical	mechanical	automatic
vacuum motor	1000W	480W	480W

Standard equipment



- PPL brush Ø 483 mm - 19"



- Front squeegee blade L.830 mm Shore 40 Th. 2.5 mm
- Rear squeegee blade L.870 mm Shore 40 Th. 3 mm



- On-board Battery charger CBHD1 24V 10A only for model code: 8.527.0007 - 8.527.0008 8.527.0013



- Maintenance free battery 12V 75Ah BT DC 5.5 only for model code: 8.527.0013

Other available versions:

- 8.527.0013 - A5 Evo 50B with batteries and battery charger
- 8.527.0007- A5 Evo 50B with battery charger

A5 EVO

- Very compact scrubbing machines suitable to work for the maintenance cleaning of limited-size areas (up to 1.500 m²)
- Especially suitable for cleaning: car shops, sales points, gym, health care
- Control panel with operator presence safety system
- Low level battery indicator: brush/vacuum and traction progressive cut off
- Solution water filter and solenoid valve (battery model only)
- Easy access to the battery compartment
- Quick drain and easily inspectable recovery tank
- Non-marking wheels
- Roto-molded polyethylene tanks, shock and acid resistant
- The lower tank also serves as battery compartment
- Low noise operation thanks to the protected positioning of vacuum motor.

Walk-behind floor scrubber driers



Powerful gearmotor; metal brush plate with integrated plastic splash guard/ bumper.

The outflow of the detergent solution is controlled by a solenoid valve. The actuation of the solenoid valve is operated by the control lever, avoiding the detergent solution outflow when the brush is stopped during the interruptions of work.



Renovated squeegee with new pressure adjusting system. The squeegee blades are easily replaceable without the use of tools. Quick and easy squeegee coupling through the two large knobs; the squeegee is released without any damage in the

event of accidental impact. Easy and intuitive controls. The outflow of the cleaning solution is easily controlled using the mechanical lever placed on the control panel. Inspectable mesh filter to trap any existing solid body in the cleaning solution.



Optional accessories:

- 2 x Tubular battery Pb-acid 12V 118Ah C5



- 2 x GEL Battery 12 MFP 105 12V 105Ah C5




- Polyurethane front blade L.830 TH. 3
- Polyurethane rear blade L.870 TH. 4



- Tynex brush Ø 483 mm-19"
- PPL 0,03 brush Ø 483 mm-19"
- PES brush Ø 483 mm - 19"



- EWU pad driver Ø 483 mm-19"



- Abrasive pad Ø 483 mm-19" - beige (5 pcs.)
- Abrasive pad Ø 483 mm-19" - green (5 pcs.)
- Abrasive pad Ø 483 mm-19" - black (5 pcs.)



- Extension electric cord 15 m with Schuko plug



PROFESSIONAL LINE

Lamers Reinigingstechniek B.V.

Ambachtsweg 2
7021 BT ZELHEM
+31 (0)314 623 341
info@lamersequipment.nl