

A13 R Essential

NEW



Standard equipment



A13 R 75

- 2 x PPL brush Ø 360 mm - 14"



A13 R 85

- 2 x PPL brush Ø 430 mm - 17"



A13 R 75

- Front squeegee blade L.925 mm Shore 40 Th. 3 mm
- Rear squeegee blade L.1015 mm Shore 30 Th. 4 mm

A13 R 85

- Front squeegee blade L.1027 mm Shore 40 Th. 3 mm
- Rear squeegee blade L.1150 mm Shore 33 Th. 4 mm



Watch the video on youtube:
www.youtube.com/fasavideo

Technical data:	A13 R 75 Essential	A13 R 85 Essential
Code	8.574.4002	8.574.4004
power supply	24 V DC	24 V DC
scrubbing width	750 mm	850 mm
squeegee width	900 mm	900 mm
max working capacity	3750 m ² /h	4100 m ² /h
detergent tank capacity	110 l	110 l
recovery tank capacity	130/155 l.	130/155 l.
traction	600W/automatic	600W/automatic
vacuum motor	1300 mmH ² O/400W	1300 mmH ² O/400W
brush motor	2 x 400 W	2 x 400 W

A 13 R Essential

- Capable to work for the maintenance and deep cleaning of large areas (up to 3.700 m²) with a very important reduction of cost of cleaning
- More than 50 kg of constant pressure on the brushes
- Large load tank capacity, resulting in reduced number of stops and maximum use of battery charge for effective operation of the machine
- Compact size (810 mm)
- Stability even when fully loaded, front independent wheel drive with tight steering radius
- Recovery tank control window for cleaning and easy ordinary maintenance
- Easy access to electrical components
- Automatic device that stops brushes and detergent water outflow when the machine is stationary
- Self-levelling brushes

Ride-on floor scrubber driers



The detergent water tank serves as battery compartment, allowing the housing of great capacity batteries granting continuous working time up to 4-5 hours. Large capacity shock and acid proof polyethylene tank (110 l) improves productivity avoiding frequent refilling

and idle time. Simple and intuitive controls reduce operator's training time. Easy mechanical brush plate and squeegee lifting system, for low maintenance costs. The enbloc brush plate apply a very high pressure (50 kg) to the floor, strongly and deeply removing any kind of dirt.



New control panel with digital controls and display. Digital display: with hour meter, battery charge level indicator, empty water tank level indicator and forward/reverse traction indicator. Speed control adjustment, horn, suction motor switch with delayed switch-off, brush plate lifting/lowering

selector switch, brush motor switch. The ergonomic and comfortable shape of the machine allows the operator to work effortless for a long time, improving productivity.



Optional accessories:



- 4 x Tubular battery Pb-acid 6V 180Ah C5 + 2 x connection cable batteries



- 4 x GEL Battery 6 MFP 180 6V 180Ah C5 + 2 x connection cable batteries



- Battery Charger 24V 25A 220-240/50-60



- On-board Battery charger kit - 24V - 20A



- Polyurethane front blade L.925 TH.3 Sh.40
- Polyurethane rear blade L.1015 TH.4 Sh.40
- Polyurethane front blade L.1027 TH.3
- Polyurethane rear blade L.1150 TH.4



- Tynex brush Ø 360 mm-14"
- PPL 0,03 brush Ø 360 mm-14"
- PES brush Ø 360 mm - 14"
- Tynex brush Ø 430 mm-17"
- PPL 0,03 brush Ø 430 mm-17"
- PES brush Ø 430 mm - 17"



- EWU pad driver Ø 380 mm-15"
- EWU pad driver Ø 406 mm-16"



- Ø 380 mm - 15"- beige (5 pcs.)
- Ø 380 mm - 15"- green (5 pcs.)
- Ø 380 mm - 15"- black (5 pcs.)
- Ø 406 mm - 16"- beige (5 pcs.)
- Ø 406 mm - 16"- green (5 pcs.)
- Ø 406 mm - 16"- black (5 pcs.)

PROFESSIONAL LINE

Lamers Reinigingstechniek B.V.

Ambachtsweg 2
7021 BT ZELHEM
+31 (0)314 623 341
info@lamersequipment.nl